

PVS-75 (208 V)

PVS-75 (240 V)

PVS-75 (480 V)

Unparalleled Performance

With their advanced system intelligence, next-generation Edge™ MPPT technology, and industrial-grade engineering, PowerGate Plus inverters maximize system uptime and power production, even in cloudy conditions.

Power Efficiency

Power Level	Output Power ¹	Efficiency ²
10%	7.5 kW	92.6%
20%	15 kW	95.6%
30%	22.5 kW	96.3%
50%	37.5 kW	96.7%
75%	56.25 kW	96.6%
100%	75 kW	96.3%

¹ 315V minimum ² 240V model

Edge MPPT

Provides rapid and accurate control that boosts PV plant kilowatt yield

Provides a wide range of operation across all photovoltaic cell technologies

Printed Circuit Board Durability

Wide thermal operating range: -40° C (-40° F) to 85° C (185° F)

Conformal coated to withstand extreme humidity and air-pollution levels

Proven Reliability

Rugged and reliable, PowerGate Plus PV inverters are engineered from the ground up to meet the demands of large-scale installations.

Low Maintenance

Modular components make service efficient

Safety

UBC Seismic Zone 4 compliant

Built-in DC and AC disconnect switches

Integrated DC two-pole disconnect switch isolates the inverter (with the exception of the GFDI circuit) from the photovoltaic power system to allow inspection and maintenance

Built-in isolation transformer

Protective covers over exposed power connections

PV Inverters | PowerGate[®] Plus 75 kW



PowerGate Plus 75 kW Specifications			UL/CSA
Input Parameters			
Maximum Array Input Voltage	600 VDC		•
Input Voltage Range (MPPT; Full Power)	315–600 VDC		•
Maximum Input Current	248 ADC		•
Output Parameters			
Output Voltage Range (L-L)	183–229 VAC	208 VAC	•
	211–264 VAC	240 VAC	•
	422–528 VAC	480 VAC	•
Nominal Output Voltage	208 VAC		•
	240 VAC		•
	480 VAC		•
Output Frequency Range	59.3–60.5 Hz		•
AC Voltage Range (Standard)	-12%/+10%		•
Nominal Output Frequency	60 Hz		•
Number of Phases	3		•
Maximum Output Current per Phase	208A	208 VAC	•
	181A	240 VAC	•
	91A	480 VAC	•
CEC-Weighted Efficiency	96%		•
Maximum Continuous Output Power	75 kW (75 kVA)		•
Tare Losses	65.36 W	208 VAC	•
	71.84 W	240 VAC	•
	69.5 W	480 VAC	•
Power Factor at Full Load	>0.99		•
Harmonic Distortion	<3% THD		•

• Standard ◦ Optional



Output Options

PowerGate Plus 75 kW

UL/CSA	208 VAC Output
	240 VAC Output
	480 VAC Output

Streamlined Design

With all components encased in a single, space-saving enclosure, PowerGate Plus PV inverters are easy to install, operate, and maintain.

Single Cabinet with Small Footprint

Convenient access to all components

Large in-floor cable glands make access to DC and AC cables easy

Rugged Construction

Engineered for outdoor environments

Output Transformer

Provides galvanic isolation

Matches the output voltage of the PV inverter to the grid

PowerGate Plus 75 kW Specifications		UL/CSA
Temperature		
Operating Ambient Temperature Range (Full Power)	-20° C to +50° C	•
Storage Temperature Range	-30° C to +70° C	•
Cooling	Forced Air	•
Noise		
Noise Level	<65 dB(A)	•
Combiner		
Number of Inputs and Fuse Rating	5 (100 ADC)	○
	6 (80 ADC)	○
Inverter Cabinet		
Enclosure Rating	NEMA 3R	•
Enclosure Finish (14-Gauge, Powder-Coated G90 Steel)	RAL-7032	•
Cabinet Dimensions (Height x Width x Depth)		80" x 57" x 30.84"
Cabinet Weight		2,150 lbs.
Transformer		
Integrated Internal Transformer		•
Low Tap Voltage ¹	20%	•
Testing and Certification		
UL1741, CSA 107.1-01, IEEE 1547, IEEE C62.41.2, IEEE C62.45, IEEE C37.90.1, IEEE C37.90.2		•
UBC Zone 4 Seismic Rating		•
Warranty		
Five Years		•
Extended Warranty (up to 10, 15, or 20 years)		○
Extended Service Agreement		○
Intelligent Monitoring		
Satcon PV View® Plus		○
Satcon PV Zone		○
Third-Party Compatibility		•

- Standard
- Optional

¹ The 20% boost tap on the isolation transformer increases the AC voltage output range for applications where the solar array DC operating voltage is at or near the lower end of the DC input range. This boost allows for continued inverter operation at lower DC voltage input levels.

Note: Specifications are subject to change.

©2010 Satcon Technology Corporation. All rights reserved. Satcon, Satcon S-Type, and PV View are registered trademarks, and Edge is a trademark, of Satcon Technology Corporation.

Satcon Corporate
27 Drydock Avenue
Boston, MA 02210
P: 617.897.2400
F: 617.897.2401
E: sales@satcon.com

Satcon West
2925 Bayview Drive
Fremont, CA 94538
P: 510.226.3800
F: 510.226.3801
E: sales@satcon.com

Satcon Canada
835 Harrington Court
Burlington, ON L7N 3P3
Canada
P: 905.639.4692
F: 905.639.0961
E: sales@satcon.com

Satcon Greece
Athanasiou Diakou 2 &
Marathonas Ave
Gerakas 15344
Greece
P: 30 210 6654424
F: 30 210 6654425
E: sales@satcon.com

Satcon Czech Republic
Classic 7 Business Park
Jankovcova 1037/49
170 00 Praha 7
Czech Republic
P: 420 255 729 610
F: 420 255 729 611
E: sales@satcon.com

Satcon Shenzhen China
Room 1112, 11/F, International
Chamber of Commerce,
No. 168 FuHua San Road,
FuTian District, Shenzhen, P.R.C.
518048
P: +86 755 61682588
F: +86 755 61682599
E: sales@satcon.com

Satcon Shanghai China
Room 2308, 23/F, New
HongQiao Center Building,
No. 83 LouGuanShan Road,
Changning District,
Shanghai, P.R.C.
P: 139.1811.2818
E: sales@satcon.com